

GREEN CONSTRUCTOR

ANTI-PUNCTURE SYSTEM FOR E-BIKE AND MTB



TECHNOMOUSSE

ABOUT


THE FIRST ANTI-PUNCTURE SYSTEM DESIGNED SPECIFICALLY FOR BIKES AND E-BIKES THAT GUARANTEES ABSOLUTE RIM PROTECTION, EXCEPTIONAL DURABILITY AND PERFORMANCE EVEN IN THE MOST EXTREME CONDITIONS AND OFFERS THREE MODES OF USE: TUBE, TUBELESS AND WITH SEALING LIQUIDS.

FEATURES


- CUT RESISTANT
- IT DOESN'T CRUMBLE
- IT HAS NO EXPIRATION DATE
- EASY FIT
- 100% MADE IN ITALY

BENEFITS

3 SYSTEMS OF USE




Can be used with light and ultra-light inner tubes and with light covers.



Tubeless and tubeless ready use.




Compatible with all types of tyre sealant liquids.



PROTECTION

+90%


Protects the tyre from punctures and side cuts.



GRIP

+60%

It allows the tyre to be used at much lower pressures, significantly improving the grip of the tyre and the ride feeling.



CONTROL

+70%

It absorbs most of the vibrations, ensuring a smoother, more comfortable and more precise riding.



RUN-FLAT

+100%

It perfectly supports the tyre even in the event of a puncture, simulating a pressure of about 0.5 bar inside the tyre, which allows to ride home without the risk of damaging the rim.

GREEN CONSTRUCTOR

ANTI-PUNCTURE SYSTEM FOR E-BIKE AND MTB



TECHNOMOUSSE

USE AND PERFORMANCE

XC

CROSS COUNTRY



USED WITH AN ULTRA LIGHT INNER TUBE AND SUPER LIGHT COVER GUARANTEES EXTRAORDINARY PERFORMANCE IN A VERY LOW CROSS COUNTRY PRESSURE USE SIMILAR TO TUBULAR.

AM

ALL MOUNTAIN



INDISPENSABLE IN ALL MOUNTAIN OUTINGS TO ELIMINATE THE PROBLEM OF PUNCTURES AND BE SURE TO ALWAYS GO BACK HOME RIDING.

EN

ENDURO



FOR THOSE LOOKING FOR THE MAXIMUM PERFORMANCES AT VERY LOW PRESSURES AND THE MAXIMUM RIDING PLEASURE WITHOUT THE PROBLEM OF PUNCTURES OR DEBEADING.

DH

DOWNHILL



INCREASE THE RIDING SENSITIVITY ENSURING THE MAXIMUM PROTECTION OF THE RIM EVEN DURING EXTREME USE.

Weight +/- 340 gr. per wheel (version 27.5")

COMPATIBILITY

27,5": COMPATIBLE WITH 27,5" COVERS FROM 2.25 TO 2.50

27,5" PLUS: COMPATIBLE WITH 27,5" PLUS COVERS FROM 2.60 TO 3.0

29": COMPATIBLE WITH 29" COVERS FROM 2.25 TO 2.50

29,5" PLUS : COMPATIBLE WITH 29,5" PLUS COVERS FROM 2.60 TO 3.0

INNER TUBES

Recommended inner tubes.

27,5" X 2.25 INSERT THE INNER TUBE 27,5" X 1.9

27,5" X 2.35 INSERT THE INNER TUBE 27,5" X 2.1

27,5" X 2.60 INSERT THE INNER TUBE 27,5" X 2.3


29" X 2.25 INSERT THE INNER TUBE 29" X 1.9

29" X 2.35 INSERT THE INNER TUBE 29" X 2.1

29" X 2.60 INSERT THE INNER TUBE 29" X 2.3


PRESSURES

Recommended usage pressures.



∅ 27,5" MAX 1,4 BAR

∅ 29" MAX 1,4 BAR




∅ 27,5" PLUS MAX 1,5 BAR

∅ 29" PLUS MAX 1,5 BAR

INSTALLATION

Assembly is as simple and quick as that of a normal tyre. Once installed it does not require maintenance.



ASSEMBLY IN

60

SECONDS